




SPECIFICATIONS


Nominal Voltage	12V	
Capacity (25°C)	10 hours rate (15A)	150Ah
Discharge Current Testing (25°C)	1 hours rate (82.5A)	86Ah
	3 hours rate (37.5A)	117Ah
Internal Resistance	Full Charged Battery 250C	4mΩ
Capacity Affected By Temperature	40°C	104%
	25°C	100%
	0°C	83%
	-15°C	65%
Residual Capacity (25°C)	Capacity After 3 Months Storage	91%
	Capacity After 6 Months Storage	82%
	Capacity After 12 Months Storage	65%
Charge (Constant voltage)	Cycle (25°C)	Initial Charging Current Less Than 45A Voltage 14.5~14.9V
	Float (25°C)	Charge Voltage 13.6~13.8V
Weight (Approx)	44kg	

PLANE CHART


Unit: (mm) Terminal Type: (T3)




RESIDUAL CAPACITY




DISCHARGE CURRENT 25°C



CONSTANT VOLTAGE CHARACTERISTICS



CYCLE SERVICE LIFE IN RELATION TO THE DEPTH OF DISCHARGE



CONSTANT CURRENT DISCHARGE CHARACTERISTICS (A, 25°C)

F.V/Time	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	232.0	152.5	91.0	54.6	40.7	32.2	27.2	18.5	15.4	8.3
10.2V	217.0	146.8	68.8	52.5	39.1	31.5	26.7	18.1	15.2	8.1
10.5V	205.0	142.5	84.6	51.6	38.4	30.9	26.3	17.9	15.1	8.0
10.8V	192.0	138.8	82.5	50.4	37.7	30.4	25.9	17.7	15.0	7.9

CONSTANT POWER DISCHARGE CHARACTERISTICS (Watts/Block, 25°C)

F.V/Time	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	2431	1642	1019.2	625.2	470.1	380.0	322.0	219.8	183.9	99.6
10.2V	2322	1587	980.8	601.1	451.6	371.7	316.1	215.0	181.5	97.2
10.5V	2226	1569	957.7	590.8	443.5	364.6	311.4	212.7	180.3	96.0
10.8V	2122	1547	936.4	577.1	435.4	358.7	306.7	210.3	179.1	94.8

CAPACITY FACTORS WITH DIFFERENT TEMPERATURE

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
Gel Battery	12V	50%	70%	83%	85%	90%	98%	100%	102%	104%	105%