

# DS POWER XL

120-250kVA

**3-Level Technology**

**IGBT Rectifier**

**DSP Control**



The new DS Power XL range UPS uses the latest DSP technology to be programmed to suit a wide variety of electrical environments without impacting its performance. With the DS Power XL range, efficiency, reliability and functionality are enhanced to levels unattainable with the old analogue technology. This technology does not only create significant increase in MTBF, but the capability of DSP to accurately manipulate signals at very high speed permits all the UPS subsystems to be controlled with greatly increased precision.

## GENERAL SPECIFICATIONS

- Transformerless UPS topology
- 3 Level rectifier and inverter
- High input power factor
- High efficiency up to 96.0%
- Cold start function
- Static and maintenance by-pass switch
- Output short circuit and overload protection
- External REPO switch input
- 512 events memory (512 events 45000 alarms)
- Clock and calendar (battery supported)
- Automatic battery test, remaining battery time indicator
- Temperature compensated charge system (optional)
- 2 RS232 serial ports and 12 dry contact outputs
- 3 DSP controlled modular structure
- Optional SNMP and MODBUS adaptors
- Optional graphical panel
- Full digital structure
- Small footprint
- Ecomode operation (optional)
- Fewer electronic components
- Output current limiting
- Advanced diagnostics for the input
- Selectable input/output voltage/frequency/range
- Split by-pass input (second input)
- Output DC leakage protection
- Separate DSP for inverter control
- Separate DSP for the PFC
- 3 level battery protection
- High charge current capacity
- Charge/discharge current indicator
- Advanced remote control features
- Manufactured according to EC Directive; EN62040
- 2 years warranty

## TECHNICAL SPECIFICATIONS

MODEL	DXL3120	DXL3160	DXL3200	DXL3250
Power (kVA)	120	160	200	250
<b>INPUT</b>				
Voltage		380/400 VAC 3P + N + G ± 20% (at 100% load) / - 40% (at 70% load)		
Frequency		50Hz / 60Hz, ± 10%		
Power factor (at 100% load)		≥ 0.99		
(THDI) (*)		≤ 3%		
By-pass voltage		380/400 VAC 3 Phase + N, ± 10 (adjustable)		
Input voltage THD		≤ 10%		
Protection		Fuses, Voltage & Frequency tolerance, Input power limit, Phase sequence indicator		
<b>OUTPUT</b>				
Power (kW)	108	144	180	225
Power factor		0.9		
Voltage		380/400 VAC 3P + N, ± 1% (415 VAC optional)		
Frequency		50Hz / 60Hz		
Frequency tolerance		Line synchronized: ± 2% (adjustable) / Free running: ± 0.1%		
Efficiency	up to 95.5%		up to 96.0%	
Crest factor		3:1		
Overload protection		@ 100% - 125% load : 10 min. - @ 125% - 150% load : 1 min. - > @ 150% load : by-pass		
Other protections		Advanced short circuit, Voltage tolerance, DC balance, Regenerative load, Current limiting		
Voltage THD		≤ 2% (at 100% linear load)		
<b>BATTERIES</b>				
Type		VRLA AGM / GEL / NiCd		
Nominal voltage		± 360 VDC		
Float / End of discharge voltage		± 405 VDC / ± 300 VDC		
Battery cabinet		External		
Battery ambient temperature		25°C		
Protections		3 level alarms, Battery fuses, Charging current limit, Temperature compensation (optional)		
Automatic testing		Standard every 72 hours (adjustable)		
<b>GENERAL</b>				
Standards		EN62040-1, EN62040-2, EN62040-3		
User interface		5 vector buttons, Buzzer, TFT panel		
Indicators		P-N voltage, P-P voltage, Current, Power, Crest Factor, Frequency, PF, Service Time		
Advanced		Self diagnostics, 3 maintenance time indicators, Calibration over RS232, operating hour meter		
Communication		2xRS232 serial ports, 4 standard and 8 optional DRY contact alarm relays		
Inputs		EPO input, Interactive battery panel input, Genset input		
Genset kit		Standard (programmable)		
Software		Standard T-Mon UPS Management Software (3 clients + 1 server management)		
Alarm logging		Standard: with time & date 512 events		
Protections		Power module over-temperature, Overcurrent, Temperature high alarm		
Temperature range		0°C - 40°C		
Protection degree		IP20		
Relative humidity		90% max. (non-condensing)		
Altitude		< 1000m above sea level		
Acoustic noise	< 62 dBA		< 65 dBA	
Weight without batteries (kg)	210	220	262	295
Dimensions (mm) HxWxD		1440x475x890		1440x475x970
<b>OPTIONS</b>				
Different input / output voltage		Please ask		
Transformer		Galvanic isolation transformer at the input & output (external)		
Software		T-Mon Admin Multi UPS monitoring 10-50-100-200 clients, T-Mon Server 10-50-100-200 clients		
Adaptors		SNMP, RS485, Remote monitoring panel, MODBUS (RS485 or TCP/IP), TCP/IP ,GSM/GPRS Modem, Comport multiplexer		
Parallel operation		up to 8 units		
(*) Depending on power and input/output conditions				

