

## STS 3000

Very Fast Uninterrupted Transfer

Advanced Communication

Microprocessor Control



TOWER

SERVICE /  
TECH. SUPPORT

ECO FRIENDLY



STS 3000 3 phase, 3 pole static transfer switch transfers uninterruptedly critical loads to either of two independent AC power lines. The system monitors two AC inputs. If any of them goes out of the specified tolerance, it transfers the critical load to the other. By increasing the energy quality of the systems used with STS 3000, while reducing the effects of interference and short interruptions, a backup power system is gained.

## GENERAL SPECIFICATIONS

- Full digital control with microprocessor controlled structure
- 2 AC inputs with 3 phase switching
- Easy installation and maintenance
- Compact design
- Wide input voltage range
- "Break Before Make" type transfer
- Very fast uninterrupted transfer even in case of any failure ( $\leq 4\text{ms}$  for synchronized sources)
- Selectable preferred source
- Fuse-free construction with a robust, high reliability SCR
- Digitally controlled system set points
- Programmable synchronized and unsynchronized transfers
- Convenient and multifunctional front panel and diagnostic codes
- Transfer inhibit system over a certain current value
- Overload, over temperature and short circuit protections
- Convenience during maintenance and repair with Isolated Maintenance Bypass
- Remote monitoring of energy resources
- TCP / IP, SNMP, MODBUS and RS232 infrastructure for communication
- Dry-contact interface
- Internal cooling fans
- Optional external AC power supply socket outlet
- Optional SNMP adaptor

## TECHNICAL SPECIFICATIONS

MODEL	STS3050	STS3100	STS3150	STS3200	STS3250	STS3300	STS3400	STS3600	STS3800	
Nominal current	50 A	100 A	150 A	200 A	250 A	300 A	400 A	600 A	800 A	
<b>ELECTRICAL DATA</b>										
Input voltage (Ph-Ph)	380/400/415 VAC 3P + N + G									
Input voltage tolerance	180-264 VAC (PH-N)									
Input frequency	50Hz / 60Hz									
Input frequency range	48-65Hz (upper and lower limits adjustable)									
Efficiency (at full load)	> 99%									
Input voltage THD	< 10%									
Transfer type	"Break before make"									
Transfer methods available	Automatic / Manual / Remote									
Transfer control	synchron									
	with adjustable delay (non synchron)									
	zero current (non synchron)									
Transfer time	< 4 msn for synchronous sources									
	< 10 msn for non-synchronous sources									
Switching type	3 phase switching									
Output current crest factor	3:1									
Admissible overload	0% - 100% continuous									
	101% - 150% 1 min.									
	151% - 200% 10 seconds									
	> 200% 250 msec									
Protections	Output overload and short circuit protection, Overtemperature protection, Backfeed protection, SCR fault protection									
LCD panel and mimic	Standard									
Communication	RS232 standard, RS485 optional, SNMP optional									
TCP/IP connection	Optional									
Dry contacts	4 programmable relay outputs									
Two serial ports	Optional									
Temperature sensor	Standard for internal cabinet temperature									
<b>ENVIRONMENTAL DATA</b>										
Cooling	Forced cooling (redundant fans)									
Operating temperature	0°C - 40°C									
Storage temperature	-10°C up to +50°C									
Relative humidity	90% max. (non condensing)									
Protection degree	IP20									
Standards	EN62310-1, EN62310-2									
Acoustic noise	< 52 dBA			< 55 dBA				< 60 dBA		
<b>MECHANICAL DATA</b>										
Weight (kg)	139	145	165	195	205	230	240	340	520	
Dimensions (mm) HxWxD	1500x680x540			1770x680x585				1905x915x725	1900x1250x850	